

Annexure for tenders DUE ON 20.10.2011

TENDER NO 53.11.5216

Description - A set of Out side Micrometers.

Sr. No.	Description	Qty.
01	Out side Micrometer Range = 50 to 75 mm Model No. Mitutoyo Order No. 193 – 113 least count 0.01 mm.	01 nos.
02	Out side Micrometer Range = 75 to 100 mm Model No. Mitutoyo Order No. 193 – 114 least count - 0.01 mm.	02 nos.
03	Out side Micrometer Range = 225 to 250 mm Model No. Mitutoyo Order No. 193 – 110 least count - 0.01 mm.	02 <u>nos</u>
04	Out side Micrometer Range = 150 to 300 mm Model No. Mitutoyo Order No. 340 – 512 – 30 least count - 0.01 mm.	02 nos.

Annexure for tenders DUE ON 20.10.2011

TENDER NO 53.11.5221

Description :- A set of Direct on line starters.

Sr. No.	Description	Qty.
01	Direct on line starter 10HP, Coil Voltage-415 VAC-3 50 Hz, Type- DOLME1, Cat No. IHPDOLM1.0	05 Nos.
02	Direct on line starter 5HP, Coil Voltage-415 VAC-3 50 Hz, Type- DOLKE1, Cat No. IHPDOLK1.0	05 Nos.
03	Automatic Star- Delta Starter 20HP, 415 VAC-3 50 Hz, Type- ASTME 2, Cat No. IHPASDM 2.0	02 Nos.
04	Direct on line starter 30HP, Coil Voltage-415 VAC-3 50 Hz, OLR Range 340 to 51.0A. Type- DOL50E 3, Cat No. IHPDOLU..0	01 No.

Annexure for tenders DUE ON 20.10.2011

TENDER NO 53.11.5242

Description:- A set of electric spares suitable for Kirloskar Electric Screw Air compressor for Model No. KES 45/13.

Sr.No.	Description
1.	AC power contactors 415 V, 50 HZ 3 Ph. Operating voltage 230 VAC.
(i)	Rating 85 A type 3 TF 4922 – 0 AZ A01 Auxilary contact 2 NO + 2 NC
(ii)	Rating 45 A type. 37 F 4602 – 0 A Z A01 Auxilary contact 2 NO + 2 NC
(iii)	Rating 9 A type – 3 TF 30 – 10 – 0A Auxilary contact 1 NO + 1 NC

Annexure for tenders DUE ON 20.10.2011

TENDER NO 53.11.5243

Description:- A set of electric spares suitable for Kirloskar Electric Screw Air compressor for Model No. KES 45/13. one set consisting of two nos.each items.Over load relay contactor mounting.

Sr No.	Description
1	Current setting range 63 A to 80 A, type – 3UA 5800 – 2UZ 1
2	Current setting range 4 A to 6.3 A, type – 3UA 5000 – 1G
3	MCB- 2 pole 3 KA current rating - 40 A, voltage – 240/415 V 50 HZ Part No. 5 S Q25107 YA 40.
4	MCB- 4 pole 3 KA current rating - 63A, reference No. 5 TE 39117 Y
5	Start delta timer 3 RP 1 NO inst to 1 NO deleyed time range 3-60 Second voltage 230 – 400V AC type 3 RP 1576 – 1 NP 208 K.

SMM (D)/NKJ