

[Annexure To tender No. 70.08.5106](#)

Set of steel wire ropes & slings. (Set consisting of ten items only)

S. No	Description of the items	Qty in Nos./mtr.
1	Steel Wire rope slings Galvanized two legged with ring on top (36 mmx135 ID) & hook at the bottom made from 14 mm diameter. 6x37 construction, Fiber core, Effective length-1.7 meter long with proof load test certificate. Capacity 3T. (ISS 2266/89)	10
2	Steel Wire rope slings Galvanized two legged with ring on top (36 mmx135 ID) & D Shackle at the bottom mild steel size 17x 20 dia. made from 14 mm diameter. 6x37 construction, Fiber core, Effective length-1.7 meter long with proof load test certificate. Capacity 3T.	10
3	Steel Wire rope slings Galvanized two legged with ring on top (28 mmx125 ID) & hook at the bottom made from 12 mm diameter. 6x37 construction, Fiber core, Effective length-02 meter long with proof load test certificate. Capacity 2T.	10
4	Steel Wire rope slings Galvanized two legged with ring on top (28 mmx125 ID) & D Shackle at the bottom mild steel size 5/8"x3/4" dia. made from 12 mm diameter. 6x37 construction, Fiber core, Effective length-02 meter long with proof load test certificate. Capacity 2T.	10
5	Steel Wire rope slings Galvanized two legged with ring on top (44 mmx150 ID) & hook at the bottom made from 18 mm diameter. 6x24 construction, Fiber core, Effective length-1.75 meter long with proof load test certificate. Capacity 5T.	10
6	Steel Wire rope slings Galvanized two legged with ring on top (44 mmx150 ID) & D Shackle at the bottom mild steel size 7/8"x1" dia. made from 18 mm diameter. 6x24 construction, Fiber core, Effective length-1.75 meter long with test certificate. Capacity 5T.	10
7	Steel Wire rope slings Galvanized two legged with ring on top (56 mmx250 ID) & Hook at the bottom (at free end) steel alloy made from 26 mm diameter. 6x37 construction FMC mechanical spliced, Fiber core, Effective length-02 meter long with proof load test certificate. Capacity 10T.	10
8	Steel Wire rope slings Galvanized two legged with ring on top (60x200 ID) & D Shackle at the bottom steel alloy size 5/4"x11/8" dia. made from 25 mm diameter. 6x37 construction, Fiber core, Effective length-3 meter long with proof load test certificate. Capacity 10T.	06
9	Steel wire rope galvanized fiber core construction 6x36, tensile strength 180/ Kg/ sq mm, breaking strength 19200 Kg, size of wire 18 mm as per IS 2266/89 with proof load test certificate	140 meter
10.	Steel Wire rope slings Galvanized two legged with ring on top (67 mmx260 ID) & Hook at the bottom (at free end) steel alloy made from 32 mm diameter. 6x37 construction FMC mechanical spliced, Fiber core, Effective length-2.25 meter long with proof load test certificate. Capacity 15T.	08
IS of material should be IS2762-1982 & IS 2759-1969		