

उप मुख्य सामग्री प्रबंधक कार्यालय
Dy. CMM/CRWS/BHOPAL

No. 68.12-WB- 13

Date: 05.04.2012

निविदा बंद होने की तिथि.....

समय 14.30 बजे

24.04.2012

Tender to be closed on..... at 14:30 Hrs .

सुपुर्दगी का स्थान : उप मुख्य सामग्री प्रबंधक,सडिपुका,मेन स्टोर,भोपाल

Place Of Delivery : Dy. CMM (CRWS) BPL {AT MAIN STORES}

सुपुर्दगी अवधि : 30 दिन / भंडार उपलब्धता के अनुसार

Delivery Terms : 30 Days / Ex stock

1	68.12.5227	FRP Tray set battery Box of AC Coaches ,one set consisting of item No.3=01No.& item No.4=04Nos (Total 5Nos) to ICF Drg.No. WGSC-SC-WAC-7-1-030Alt.'E'Sheet 1&2 Col-II.	08 Nos
2	68.11.5814	Heavy duty metal type-12 pin panel mounting socket. Cat No-2499/12, Rating-12 Amp/415 V. Make-BCH/ Siemens /L&T.	10 Nos.
3	68.11.5481	" Alluminium Angle Moulding" Size -30x10x3600x2mm thick As per IS: 733/1983.	180 Kg,s
4	68.12.5006	Air blow gun similar to CP Mdoel RC 8120 Suitable for working pressure 10kg/an ² Air connection size ¼" Male BSPT.	12 Nos
5	68.12.5200	Sleeve for auxillary Head stock to IS:2062 As per Drg.No.CRWS/AB-48	3600 Nos.
6	68.12.5042	Guard Emergency Brake Valve. As per Drg. No. RDSO Drg.No. SK-73549 Alt-5	100 Nos
7	68.12.5202	"Shellac Jointing compound Spec.Rev-I"as per IS:3447/1993.(In ½ kg packing).Make-Pidilite/I.T.W.	120 KG
8	68.12.5197	Modified B.S. door RH(BEML),Furnished with lock assembly, Door latch sunken type locking plate for PAD Lock & Guard Lock ARG T, with 8 window bars for BEML Coaches." as per reference Drawing ICF drawing T-5-1-673 & ICF Drawing T-5-1-672 and sizes of door as per annexure attached.	10 Nos
9	68.12.5102	Eye for catch for B.S.Door (with slot) of BEML Coaches ,Item No.2."as per Drg.No.CRWS.K.-415 Item No.2.	150 Nos
10	68.12.5209	4Star Rating metal body storage type water heater/Geyser capacity to 10 litres,Type V,Class-I,ISI Marked complete with all accessories,test certificate & Guarantee card . Make-Bajaj/Crompton /Racold.	05 Nos

AMM/CRWS/BPL

Annexure of Tender No.68.12.5197

Modified B.S. door RH(BEML),Furnished with lock assembly, Door latch sunken type locking plate for PAD Lock & Guard Lock ARG, with 8 window bars for BEML Coaches.” Sizes of door as per annexure attached.

Ref:- ICF drawing of out door assembly,No.T-5-1-673 & ICF Drawing T-5-1-672

The required Dimension for B.S.Door (RH& LH) of beml Coaches as under as per sample available in Carpentry shop/CRWS/Bhopal.

Existing Dimension of B.S.door as per ICF Part drawing T-5-1-604,alt.h/2.	Required Dimension for modified B.S.Door (RH&LH) of BEML Coaches.
As per ICF part drawing T-5-1-604.ALT.H/2 for door frame arrangement Left Hand,dimension from bottom of door to window still is shown 682 mm, Overall length shown 1848 mm, Overall Thickness of door dshown 87.15 mm & shown other dimesion also.	<ol style="list-style-type: none">1.) As per ICF drawing No. T-5-1-604.alt.h/2 , the dimension of body side door 'from bottom to window still is required 740 mm instead of 682 mm (as shown T-5-1-604.ALT.h/2).2.) Overall length is required 1951 mm instead of 1848 mm (as shom in drawing No.T-5-1-604.alt.h/2).3.) Position of door lock from bottom of door is required 540mm.4.) Overall width is required 783 mm (as shom in drawing No.T-5-1-604.alt.h/2)5.) Overall thickness of door required 92 mm instead of 87.15 mm.6.) Lockig plate for pad lock required sunken type ,Size of sunken box will be 135mmx45mmx15mm deep (approx) & height of rivet for locking plate for pad locking will be 175 mm from bottom of door.7.) Rest of dimension will be also changed accordingly.
Required dimensions will be same for RH & LH B.S.Door.	

AMM/CRWS/Bhopal