



- NOTE :-
- 1 D.T.P.B. TO BE PASTED TO THE COMPREG WITH APPROVED BRAND OF WATER PROOF GLUE.
 - 2 NECESSARY CUTAWAY TO BE DONE TO SUIT AT SITE.
 - 3 THREAD SHOULD BE DYED AND THE COLOUR OF THREAD SHOULD MATCH WITH THE COLOUR OF REXINE THE PITCH OF STITCH SHALL BE 2 TO 3 MM.
 - 4 COLOUR OF REXINE TO BE AS PER CODE NO. ALNAC-03 STAMPED WITH INDIAN RLY. CREST TO RDSO/SK68068 ALT.2
 - 5 COMPREG TO BE TREATED AGAINST FUNGI, TERMITES MARINE BORERS & OTHER INSECT ACCORDING TO REQUIREMENTS OF PRESERVATION TREATMENT TO IS-5539-63 TYPE IX (COPPER CHROME ARSENIC COMPOSITION)
 - 6 FELT (ITEMS 4 & 5 TO BE PASTED PROPERLY ON THE FRAME WITH APPROVED BRAND OF ADHESIVE)
 - 7 D.T.P.B. TO BE DIRECTLY MOULDED AND NOT TO BE FABRICATED
 - 8 SKIN OF DTPB SHOULD BE UNIFORM WITHOUT CRACKS OR JOINTS
 - 9 REXINE SHOULD BE STITCHED IN SUCH A MANNER THAT NO FOLDS ARE VISIBLE AT THE CORNERS
 - 10 THE SEATS AND BERTH SUPPLIER MUST HAVE THE INFRASTRUCTURE FOR DTPB MANUFACTURE AND TESTING AS PER RDSO SPEC C-K607 Amndt Slib 182.
 - 11 THE SUPPLIER SHOULD FURNISH THE DETAILS OF DTPB FACILITIES IF IN HOUSE OTHERWISE SHOULD GIVE SUBSTANTIVE DETAILS OF TIE UP WITH REPUTED D.T.P.B. MANUFACTURER ALONG WITH THEIR TEST FACILITIES CRWS RESERVES THE RIGHT TO CHECK THESE FACILITIES BEFORE OR AFTER ENTERING IN TO THE CONTRACT.
 - 12 ITEM NO 9, 10, 11 SHALL BE DULL ANODISED TO IS:1868-82 TAB-1 GR. AC 10.
 - 13 IT IS AN INTERIOR FITTING ITEM SHALL HAVE ELEGANT FINISH.

ITEM NO	DESCRIPTION	QTY	MAT & SPEC
17	SLTD PAN HD TAPP SCREW STEEL ST. 4.2X16 F	72	IS:7173-83 STEEL
16	SEWING THREAD L 5000	1	IS:4223-82-66VAR L2
15	COTTON THREAD φ 3X3000	1	IS 1720-78
14	PLAIN WASHER A55	18	IS:2016-67 (ALU)
13	CSK HEAD RIVET (ALU) 5X12	18	IS 2907-1964 (ALUMINIUM)
12	NAMEPLATE	1	CCG 1188
11	ANGLE	2	IS 733-83, 63400 WP
10	ANGLE	1	IS:733-83, 63400 WP
9	ANGLE	1	IS 733-83, 63400 WP
8	SIDE REXINE 150X610		RDSO/2008/CG-07 COLOUR AS PER CODE ALNAC-03
7	TOP REXINE 830X2139		RDSO/2008/CG-07 COLOUR AS PER CODE ALNAC-03
6	DENSIFIED THERMAL BONDED POLYESTER 50X557X 1815	1	RDSO SPEC C-K607 Amndt Slib 182
5	FELT 6X66X1840		IS:1719-88 TAB-I MEDIUM
4	FELT 6X66X2850		IS 1719-88 TAG I MEDIUM
3	COMPREG PANEL 4X470X1740		RDSO SPEC C-K607 Amndt Slib 182
2	SLTD PAN HD TAPP SCREW ST. 3.5X16-F	2	IS:7173-83 STEEL
1	FRAME	-	CRW/SK 884

1 REFERENCE RCF DRAWING AE-61321 ALT. 3 AND SE61322 ALT. A
 2 DRAWING DRAWN AS PER DETAILS GIVEN BY SSE CARP. LETTER NO Regn FOR PREPARATION DRAWING DATED 13.08.2010

AWM	<i>[Signature]</i>	TRANSVERSE SEAT (LOWER BERTH) FOR G.S. C.N ICF/RCF TYPE COACHES	 24/9/10 WEST CENTRAL RAILWAY COACH REHABILITATION WORK SHOP NISHAT PURA BHOPAL
SSE/FOR	<i>[Signature]</i>		
SSE	<i>[Signature]</i>		
JEDRG	<i>[Signature]</i>		
DRN	<i>[Signature]</i>	DRG. NO. CRW/SK-885	