

उप मुख्य सामग्री प्रबंधक कार्यालय
Dy. CMM/CRWS/BHOPAL

No. 68.12-WB- 47

Date: 19.12.2012

Tender to be closed on...**01.01.2013**..... at 14:30 Hrs .

सुपुर्दगी का स्थान : उप मुख्य सामग्री प्रबंधक,सडिपुका,मेन स्टोर,भोपाल
Place Of Delivery : Dy. CMM (CRWS) BPL {AT MAIN STORES}
सुपुर्दगी अवधि : 30 दिन ६ भंडार उपलब्धता के अनुसार
Delivery Terms : 30 Days / Ex stock

1	68.12.5893	Set of Elbo & Nipple M.S.Heavy duty size 20x20mm ,IS:1239 Part-II/1982 (One set consisting-01No.each).as per Drg.N. CRW/AB-53.	400 Nos
2	68.12.5894	Screwing die Size-1"-2", 11TPI H.S.S. Rockwell Hardness HRC-58-62, Suitable for Inder power Electric pipe Threading Machine 140'A' One Set Consisting of =04 Nos.	12 Set's
3	68.12.5895	PVC Insulated sheathed industrial cable copper conductor 1100volts grade confirming to IS:694/1990 ISI Mark with amendment,size -3 core/6Sqmm (84/0-30).Make-Plaza /HPL / Cab con India/IMT Cable.	200 Mtrs.
4	68.12.5896	PVC Insulated six core flexible copper cable of different colour code conductor ,size-24/0.20mm,area-0.75sqmm ,voltage-1100volt,as per IS-694-1990,overall dia-10mm,Make-Cabcond India ,PS Enterprises/Skyline/hpl India /IMT.	800 MTRS
5	68.12.5898	Slotted bit suitable for pneumatic screw driver machine .Model=22P-500 IR Make.Bit consisting Dimension blade Thickness=1.17mm ,Body Dia=7.9mm ,over all LENGTH=49MM. Make=Vessel/CP/IR Wadco.	200 Nos
6	68.12.5899	Air Inlet Nipple ,Size=¼inch BSP Thread for 8mm bore Hose,Barbed Type Nipple in brass material .As per Approved sealed sample attached.	200 Nos
7	68.12.5900	Pipe Packing wooden (Small) IS:K-2-66 as per Drg.No.CRW/SK-86.	3000 Nos.
8	68.11.5902	Chlorinated PVC Acid proof Handgloves size-14" as per specification-OS/Safety/006 Spec.No.11.	200 Pairs
9	68.12.5903	Half Face Piece silicon Respirator as per specification – OS/Safety/006 Spec.No.14	22 Set
10	68.12.5904	Disposable type Respirator with valve as per specification – OS/Safety/006 Spec.No.16	200 Nos
11	68.12.5905	Set of Compartment door (with grill) for AC Sleeper coaches (One set consist one no.LH to drawing No. CC56419 alt'c' & one no. RH to drawing No. CC56408 alt'd' item No. 9 should be Godrej make heavy duty	06 Set
12	68.12.5906	Gas Nozzle 17mm std. Part No. 4651691969 for ESAB Make Co2 welding torch model PSF 405.	30 Nos
13	68.12.5907	Set of Gas cutting Nozzles,Copper sizes 1/16" &3/64"or oxy-acetylen gass cutting blowpipe of item M/s ESAB or M/s Asha (Original) or M/s or M/s Premier Make with OEM authorized certificate.	150Set

14	68.12.5908	Fully insulated open head electrode holder, 600 Amps.of Make – ESAB or JACKSON, USA or LINCOLN, USA. Model: similar to JACKSON A3-S with feature (a) suitable for 95 mm core dia, Aluminium cable (b) Holder should have embossed/ cast. Identification mark of manufacture of holder. Supplier should submit OEM certificate at the time of supply.	300 Nos
15	68.12.5909	CO2 Cylinder valve brass size 25.4mm dia taper thread without wheel ,IS:3224,ISI Mark,month & year of Manufacture,working pressure and chemical name of gas should be embossed on body of valve of M/S Vnaz or Bharat or Techno make with test certificate	100 Nos
16	68.12.5910	Tip adopter M8,Part No. 4651691989 of Co2 welding torch Model PSF-405 of Esab make.	30 Nos
17	68.12.5912	Pressure screw for oxyzen,DA & CO2 Single stage regulator,size 8mm of brass confirming to IS:292-1983.	200 Nos
18	68.12.5913	Single compression brass cable gland (Long Nipple) Similar to Jainson cat No. J.C.'1'L.N. Core size in Sqmm (2.5x7,10,12)25mm.	1000 Nos
20	68.12.5814	Set of Alluminium Anodised channel moulding to Drg.No. –AE-43132,Alt.-c width 23mm instead of 12mm for safety wall of AC Coaches.	112 set.
21	68.12.5851	Railway Carriage Fan 110Volt AC,225MM Sweep wall bracket type as per IS:6680-1992 Deviation as per Annexure 'H'(Rev in Dec-2005) Fan Guard shall be crashworthy and blade should be made of M.S.Material the complete fan including fan fixures (Guard &Blade)Shalle be power quoted to silver Ash finish.	28 Nos
22	68.12.5792	Flam proof cotton canvas size-91.4cm width in suclad FPC-700,As per RDSO, Spec.No. RDSO/PE/SPEC/AC/0136-2009 (Rev-0) & As per IS:1424-83 Varity-2.	120 Mtrs.
23	68.12.5854	Portable Combustible Gas Detector ,with all standard accessories, spares with 01 No.extra sensar of pulsecho model No. DGC-250,Victory Model No. V-700 OR Prism Model No. XP-3110 Make.	01 Nos
24	68.12.5844	Metric Thickness Gauge Range-0.05 to 1 mm,28 leaves,(Short leaf) each leaf is mark with its thickness. Make- Mitutoyo or Mahr.	06 Nos
25	68.12.5831	Mosquito net stainless steel best quality with average width of opertures not more than 1.4mm in both direction with wire of 0.55minimum.	1400 sqfeet.
26	68.12.5325	Set of Ball bearing for machinery and plant. One set consisting bearing No. 7210=06Nos,Bearing No. 6019=02Nos.,Bearing No.6210=12Nos,Bearing No.6000.2ZR=25 Nos and Bearing No.6203.2ZR=25 Nos .Make-SKF/FAG/NBC only . Proof purchase from OEM Dealer	01 Set
27	68.12.5853	2X1.5 colour Black (White core numbered black) electron beam irradiated 750 V/1 KV to specification No.EDTS-132,REV-C,AM-3,Data sheet-4,RDSO approved make-Nicco/Kolkata,Huber & Suhner AG,Radiant RSCC,Siechem Technologies,OEM Certificate should be submitted along with supply of material.	500 Mtrs

AMM/CRWS/BPL

Annexure of Tender No.68.12.5897 due on 01.01.12
Set of Alluminium conduit ,Hex lock nut,coupler,internally screwed bushes for Underframe wiring of AC & Non AC Cpaches. One set is consisting of following 12 items.

Sr.No.	Item	Unit	QTY per set
1	Alluminium conduit 50mm threadable quality designation 63400 WP,2.5 MM thick to IS: 1285-2002,Suitable for electrical,dimensions confirming to IS:9537-81 (Part-2) in 03 Mtrs length conduit shall be threaded 50mm length at both ends.	Mtrs	417
2	Alluminium conduit 32mm threadable quality designation 63400 WP,2.5 MM thick to IS: 1285-2002,Suitable for electrical,dimensions confirming to IS:9537-81 (Part-2) in 03 Mtrs length conduit shall be threaded 50mm length at both ends.	Mtrs	270
3	Alluminium conduit 20mm threadable quality designation 63400 WP,2.5 MM thick to IS: 1285-2002,Suitable for electrical,dimensions confirming to IS:9537-81 (Part-2) in 03 Mtrs length conduit shall be threaded 50mm length at both ends.	Mtrs	48
4	Hex locks nuts 50mm hot dipped galvanized to IS:3837-1976,Table-6 and IS:4759-1984.	Nos	352
5	Hex locks nuts 32mm hot dipped galvanized to IS:3837-1976,Table-6 and IS:4759-1984.	Nos	116
6	Hex locks nuts 20mm hot dipped galvanized to IS:3837-1976,Table-6 and IS:4759-1984.	Nos	72
7	Couplers dia 50mm (Internally screwed) hot dipped galvanized IS:2667-1988,Table-1 and IS:4759-1984.	Nos	106
8	Couplers dia 32mm (Internally screwed) hot dipped galvanized IS:2667-1988,Table-1 and IS:4759-1984.	Nos	42
9	Couplers dia 20mm (Internally screwed) hot dipped galvanized IS:2667-1988,Table-1 and IS:4759-1984.	Nos	6
10	Internally screwed bushes 50mm to ICF Drg.No. ICF/SK-7-2-230 Item No. 13 Alt-"A"	Nos	352
11	Internally screwed bushes 32mm to ICF Drg.No. ICF/SK-7-2-230 Item No. 11 Alt-"A"	Nos	116
12	Internally screwed bushes 20mm to ICF Drg.No. ICF/SK-7-2-230 Item No. 9 Alt-"A"	Nos	72

Dy.CMM/CRWS/BPL