

Set of steel wire rope & Slings with competent person approved test certificate,  
 One set consisting of 12 items in Qty 67 Nos.  
 Vide Requisition No. 57310268 date 16.07.12

ANNEXURE

SN.	Description of items	Qty/Set
1.	Two legged steel wire rope slings 14mm dia x 1.7 Meter long, 6x37 construction, Capacity=3.0 Tons, Main ring of 36x135mm at top, Hook at bottom.	08 Nos.
2.	Two legged steel wire rope slings 14mm dia x 1.7 Meter long, 6x37 construction, Capacity=3.0 Tons, Main ring of 36x135mm at top, D-shackle MS Size 17x20mm at bottom.	08 Nos.
3.	Four legged steel wire rope slings 14mm dia x 3.0 Meter long, 6x37 construction, Capacity=3.0 Tons, Main ring of 36x135mm at top, Hook at bottom.	06 Nos.
4.	Four legged steel wire rope slings 14mm dia x 3.0 Meter long, 6x37 construction, Capacity=3.0 Tons, Main ring of 36x135mm at top, D-shackle MS Size 17x20mm at bottom.	02 Nos.
5.	Two legged steel wire rope slings 12mm dia x 2.0 Meter long, 6x37 construction, Capacity=2.0 Tons, Main ring of 28x125mm at top, Hook at bottom.	08 Nos.
6.	Two legged steel wire rope slings 12mm dia x 2.0 Meter long, 6x37 construction, Capacity=2.0 Tons, Main ring of 28x125mm at top, D-shackle MS Size 5/8" x 3/4" at bottom.	08 Nos.
7.	Two legged steel wire rope slings 18mm dia x 1.75 Meter long, 6x24 construction, Capacity=5.0 Tons, Main ring of 44x150mm at top, Hook at bottom.	06 Nos.
8.	Two legged steel wire rope slings 18mm dia x 1.75 Meter long, 6x24 construction, Capacity=5.0 Tons, Main ring of 44x150mm at top, D-shackle MS Size 7/8" x 1" at bottom.	06 Nos.
9.	Two legged steel wire rope slings 26mm dia x 2.0 Meter long, 6x37 construction, Capacity=10 Tons, Main ring of 56x200mm at top, Steel Alloy Hook at bottom.	04 Nos.
10.	Two legged steel wire rope slings 25mm dia x 3.0 Meter long, 6x37 construction, Capacity=10 Tons, Main ring of 60x150mm at top, D-shackle Steel Alloy Size 5/4" x 1-1/8" at bottom.	04 Nos.
11.	Two legged steel wire rope slings 32mm dia x 2.25 Meter long, 6x37 construction, Capacity=15 Tons, Main ring of 67x260mm at top, Steel Alloy Hook at bottom.	06 Nos.
12.	Steel wire rope finish galvanised, 18mm dia, 6x36 construction fibre main core. Minimum braking strength 19200 kgf. Conforming to IS: 2266 of 2002.	140 Mtrs.

Two legged steel wire rope slings conforming to IS:2762 of 2009, Main ring at top, Hook/D-Shackle at other end, Made from galvanised wire rope having fiber core, Right hand ordinary Lay, Tensile strength 1770 N/Sqmm conforming to IS:2266 of 2002, Mechanical splicing conforming to IS:5245 (Part II) of 1971, Hook conforming to IS: 2759 of 1969, Ordinary Thimble conforming to IS:2315 of 1978, D shackle conforming to IS:6132 of 2003.

*SSE/M-4*

ADBE/TRS/ET  
 (म.प्र.सं.) उ.प्र.सं. संस्था  
 (M.P.S.) U.P.S. Sanstha  
 (म.प्र.सं.) उ.प्र.सं. संस्था