

65-13-8027

TECHNICAL SPECIFICATION

Hydraulic power equipment with accessories and tooling arrangement for using Huck/Avdelok fasteners

163

23

1	Major Parameter.	<p>Capability: For using Huck/Avdelok fasteners from 1/2" (12 mm) to 7/8" (22 mm) in lieu of rivets on Railway Wagons during the course of carrying out POH/ROH. Power unit must have Inbuilt pressure gauges for Pull & Return pressure.</p> <p>Working pressure: Pull - 10000psi Return - 2800psi</p> <p>Delivery: 3.1 LPM</p> <p>is suitable for reduces operator fatigue.</p>
2	Minor Parameter.	<p>Power: Three phase 380/415 V, 5.3 Amp/ 50 Hz</p> <p>Length-870 mm approx.</p> <p>Width-360 mm approx.</p> <p>Height-700 mm approx.</p>
3	Concomitant accessories	<p>1. Hydraulic Installation Tool suitable for placing 1/2" (12mm) dia. Lockbolts, Stroke: 38mm approx. Weight not more than: 5kg approx.</p> <p>2. Hydraulic Installation Tool suitable for placing 3/4" (20mm) dia. Lockbolts, Stroke: 50mm approx. Weight not more than: 7 Kg approx.</p> <p>3. Hydraulic Installation Tool suitable for placing 7/8" (22mm) dia. Lockbolts, Stroke: 50mm approx. Weight not more than: 12 Kg approx.</p> <p>4. Nose assembly suitable for 1/2" (12 mm)</p> <p>5. Nose assembly suitable for 3/4" (20 mm)</p> <p>6. Nose assembly suitable for 7/8" (22mm)</p>
4	Optional accessories.	<p>No</p>
5	Spare.	<p>Essential consumable spares related to operation & maintenance for at least one year.</p>
6	AMC requirement	<p>No.</p>
7	Warranty requirement.	<p>AS per IRS General condition.</p>
8	Special requirement.	<p>No</p>

डॉ. ए. ए. ए. (पि.)
 डॉ. ए. ए. ए. (पि.)
 डॉ. ए. ए. ए. (पि.)
 डॉ. ए. ए. ए. (पि.)

Handwritten notes and signatures at the top right of the page.