

7 20

	<ul style="list-style-type: none"> ● RFC 4346 TLS Protocol Version 1.1
Encryption	<ul style="list-style-type: none"> ● WEP and Temporal Key Integrity Protocol-Message Integrity Check (TKIP-MIC): RC4 40, 104 and 128 bits (both static and shared keys) ● Advanced Encryption Standard (AES): CBC, CCM, Counter Mode with Cipher Block Chaining Message Authentication Code Protocol (CCMP) ● DES: DES-CBC, 3DES ● Secure Sockets Layer (SSL) and Transport Layer Security (TLS): RC4 128-bit and RSA 1024- and 2048-bit ● DTLS: AES-CBC
Authentication, Authorization, and Accounting (AAA)	<ul style="list-style-type: none"> ● IEEE 802.1X ● RFC 2548 Microsoft Vendor-Specific RADIUS Attributes ● RFC 2716 PPP EAP-TLS ● RFC 2865 RADIUS Authentication ● RFC 2866 RADIUS Accounting ● RFC 2867 RADIUS Tunnel Accounting ● RFC 3576 Dynamic Authorization Extensions to RADIUS ● RFC 3579 RADIUS Support for EAP ● RFC 3580 IEEE 802.1X RADIUS Guidelines ● RFC 3748 Extensible Authentication Protocol ● Web-based authentication ● TACACS support for management users
Management	<ul style="list-style-type: none"> SNMP v1, v2c, v3 RFC 854 Telnet RFC 1155 Management Information for TCP/IP-Based Internets RFC 1156 MIB RFC 1157 SNMP RFC 1213 SNMP MIB II RFC 1350 TFTP RFC 1643 Ethernet MIB RFC 2030 SNMP RFC 2616 HTTP RFC 2665 Ethernet-Like Interface types MIB RFC 2674 Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering, and Virtual Extensions RFC 2819 RMON MIB RFC 2863 Interfaces Group MIB RFC 3164 Syslog RFC 3414 User-Based Security Model (USM) for SNMPv3 RFC 3418 MIB for SNMP RFC 3636 Definitions of Managed Objects for IEEE 802.3 MAUs private MIBs
Management Interfaces	<ul style="list-style-type: none"> ● Designed for use with Wireless Control System ● Web-based: HTTP/HTTPS individual device manager ● Command-line interface: Telnet, SSH, serial port
Interfaces and Indicators	<ul style="list-style-type: none"> ● Console port: RJ-45 connector ● Network: Four 1 Gbps Ethernet (RJ-45) ● LED indicators: Link Activity (each 1 Gigabit Ethernet port), Power, Status, Alarm
Physical and Environmental	<ul style="list-style-type: none"> Dimensions: 1.73 x 8.00 x 6.75 in. (43.9 x 203.2 x 271.5mm) Weight: 3.5 lbs (with power supply) Temperature:

Ashwin (Sachin Desai)
SDE | RNet | 1st