

Dy. CMM/CRWS/BHOPAL

No. 68.13-WB-30

Date : 30.12.2013

Tender to be closed on... **03.01..2014..... at 14:30 Hrs.**

Place of Delivery : Dy. CMM (CRWS) BPL {AT MAIN STORES}

Delivery Terms : 30 Days / Ex stock

Sr.	Tender No	Description	Qty
1	68.13.5954	M 16 X 65 Hexagonal head half thread bolt galvanized having 04 mm Dia hole, Hole cotter at the distance of 08mm from threaded end with 01 No. spring washer ,01No. Nut & 01 No. split pin –size-3.7x40 mm length in assembled condition .Spec. Bolt as per IS:1363 Part –I, Spring washer IS:3063 & Nut as per IS: 1363 Part-III.	2600 Nos
2	68.13.5955	Sleeve for Auxiliary head stock as per IS:2062,As per Drg.No. CRWS/AB-48.	2000 Nos
3.	68.13.5956	CAM for Alarm signal device with groove screw-M-6X10 MM IS: 9550-1980,Cam dia 50mm-IS:2062.,fe-410. as per Drg.No.CRW/SK-AB-57 item No.1&2..	1300 Nos
4	68.13.5957	Felt pad size=7” dia, stock code No.=H2502059 Should be suitable for application in Pneumatic Angle Sander Machine as per CP-319A	25 Nos
5	68.13.5958	Set of spare parts for Pneumatic Pop Riveter C-883. Details of spares is as per Attached Annexure-'A' and should be suitable for application in machine as per CP-883 spare part mentioned in annexure.	01 Set
6	68.13.5959	Frosted toughened safety Glass for compartment door of AC Coaches as per annexure attached.	120 Nos
7	68.13.5888	Industrial safety footwear confirming to IS:15298 (Part-2),2002 with amendment No.1 or Latest classification-1 of table 1,design-B of figure-1,black upper Leather out sole made of polyurethane having resistance to Acid Alkali oil and water without nail, each safety shoe shall be clearly marked with ISI Mark at suitable place size at foot wear as per English version Size-05.	19 Pairs
8	68.13.5889	Industrial safety footwear confirming to IS:15298 (Part-2),2002 with amendment No.1 or Latest classification-1 of table 1,design-B of figure-1,black upper Leather out sole made of polyurethane having resistance to Acid Alkali oil and water without nail, each safety shoe shall be clearly marked with ISI Mark at suitable place size at foot wear as per English version Size-06.	66 Pairs
9	68.13.5890	Industrial safety footwear confirming to IS:15298 (Part-2),2002 with amendment No.1 or Latest classification-1 of table	65 pairs

		1,design-B of figure-1,black upper Leather out sole made of polyurethane having resistance to Acid Alkali oil and water without nail, each safety shoe shall be clearly marked with ISI Mark at suitable place size at foot wear as per English version Size-07	
10	68.13.5891	Industrial safety footwear confirming to IS:15298 (Part-2),2002 with amendment No.1 or Latest classification-1 of table 1,design-B of figure-1,black upper Leather out sole made of polyurethane having resistance to Acid Alkali oil and water without nail, each safety shoe shall be clearly marked with ISI Mark at suitable place size at foot wear as per English version Size-08.	37 pairs
11	68.13.5892	Industrial safety footwear confirming to IS:15298 (Part-2),2002 with amendment No.1 or Latest classification-1 of table 1,design-B of figure-1,black upper Leather out sole made of polyurethane having resistance to Acid Alkali oil and water without nail, each safety shoe shall be clearly marked with ISI Mark at suitable place size at foot wear as per English version Size-09.	03 pairs
12	68.13.5499	Open type Fuse base 400A-415V, TO IS:13703 (Part-2 Sec-1)ICF Approved sources simens KEL,C&S,L&T,GE Power or any other BIS Certified and Marked.	150 Nos
13	68.13.5964	12 mm. Dia Alloy steel GR-80 Four Legged Chain sling with main bull ring of 36 mm. Dia x160 mm.ID,Eye ring of 28 mm.Dia x100 mm. ID and Eye Hook at free ends Effective Length 3Mtrs. SWL 9Tons at 0-90 degree .Hook Opening J-75 MM. with proof Load test certificate of OEM. Anand,Supreme, EEK Or Multitech Make.	02 Nos
14	68.13.5965	Nylon bush as per Drg.No.T-3-2-640 Alt.3 Item.17.	1800 Nos
15	68.13.5966	Bracket for Anchor Link (Bolster) as per Drg.No.T-0-4-615 Alt.K&6.	300 Nos
16	68.13.5967	HSS Square tool bit S-400 (with 10%Cobalt) size-½" x6" Make-MIRINDA,T.T.or Addison with Authorized Dealer Certificate along with offer.	06 Nos
17	68.13.5968	M.S. Plain Punched Washer Size Out Side Dia= 52 mm. In side Dia = 32 mm. & Thickness 1.6 mm.	16000 Nos.
18	68.13.5969	2MTR Steel measuring tape (Steel body) with combined Graduation in matric and inches. Make—Freemans or FMI or GK.	100 Nos
19	68.13.5970	Stopper for screw soupling sporting hook as per Drg.No. T-1-2-610 Alt.a item.1.	1300 Nos
20	68.13.5971	Complete starter with copper winding suitable for Ralli wolf. Make-bench grinder,model-TG6",H.P-¼,RPM-2950,Part No. (Ralli wolf make)-810318,Make-Ralli wolf/Black & deeker.	01 No.
21	68.13.5972	Set of spares for swaraj make Fork lift Model FD-20. One set	01 Set

		consisting as per enclosed Annexure. Make –Swaraj/Simialar	
22	68.13.5973	Pedestal Grinder as per Annexure A.	01 No

Dy.CMM/CRWS/BPL

Annexure of tender No. 68.13.5958 due on 03.01.14.

Sr.No.	Description	Qty
1	Fitting vaccume hose lower C-147082.	40 Nos
2	Ring Snap CA-147121.	40 Nos
3	Body Swivel (Female)C-147120	25 Nos

Annexure of Tender No. 68.13.5972 due on 03.01.13.

Sr.No.	Part No.	Description	Qty
1	P515002A	Brake Drum	02 Nos
2	P515010	Gasket	02 Nos
3	M12816	Locking washer	02 Nos
4	M77673	Oil Seal 55x80x10.	02 Nos
5	M77695	Oil Seal 110x140x13	02 Nos
6	P515190A	Wheel Cylinder Assembly	02 Nos
7	P515173B	Adjustable Cam	04 Nos
8	P515160B	Brake Shoe Assembly	04 Nos
9	P515104	Pin	04 Nos
10	P515105	Axle Rattle Spring	04 Nos
11	P515106	Axle Rattle Cap.	08 Nos
12	P515107	Retainer Washer	04 Nos

Dy.CMM/CRWS/BPL

Specification of tender No. 68.13.5973 due on 03.01.14, Annexure-A.

Pedestal Grinder direct driven with inbuilt motor 3.00 HP, 2.25 KW, 3 Phase 4.5 Amp, 415 Volt with Grinding wheel size 350 x 50 x 31.75mm one side rough & other side medium fitted with eye shield, Siemens starter, wheel guard, std. tool rest plate.

1.RPM -1400-1500

2.Wheel central distance - 600 mm to 650 mm

3.Center height- 900 mm to 1000 mm

Dy.CMM/CRWS/BPL

E-Mail : dycmmpps@gmail.com