

Dy. CMM/CRWS/BHOPAL

No. 68.13-WB-41

Date : 03.03.2014

Tender to be closed on... **11.03..2014..... at 14:30 Hrs .**

Place of Delivery : Dy. CMM (CRWS) BPL {AT MAIN STORES}

Delivery Terms : 30 Days / Ex stock

Note also. : Rates should be quoted in words as well as in figures

Sr.	Tender No	Description	Qty
1	<u>68.14.5154</u>	Set of spares for Jost make platform truck. one set consisting as per enclosed annexure.	01 Set
2	<u>68.14.5155</u>	LUX meter hand held as annexure 'A' attached Make LUTRON / EXTECH	02 Nos
3.	<u>68.14.5156</u>	Alluminium P.G. Clamp assembly for ACSR in pair complete with Nut & Bolts as per sample.	30 Pair
4	68.14.5158	Spherical Roller Bearing No. 22212 E1AM for EOT crane. Make SKF / FAG. Authorised dealer certificate to be submitted with offer.	12 Nos
5	68.14.5159	Double Row Spherical Roller Bearing No. 22220 E1 for Traversar Machine. Make SKF / FAG authorised dealer certificate to be submitted with offer.	06 Nos
6	68.14.5161	Anaerobic adhesive for threaded fasteners (Thread locking) to RDSO/Specn C-8517 (Rev-1) of make Anabond -122 OR Loctite -243 (OR) Hereon nuts 'N',Bolts-434 in 50ML ,TUBE,THE TYPE OF ADHESIVE,DATE OF Manufacturing, Expiry and batch No. Shall be printed on the tube. Expiry date should be Exist more than one year at the time of delivery No other make/Brand is acceptable.	40 Nos
7	68.14.5162	Laminated safety plain transparent glass, size 1202 x 562 x 5 mm thick x 1250 diagonal with edge smoothly grinded, as per IS : 2553 part I.	81 Nos
8	68.14.5164	Heavy Duty polyster round sling 20 mm dia of endless type, capacity 02 Ton, effective length 02 meter circumferential length 04 meter with manufacturers or NABL accredited lab, test certificate, Secure lift, KHR or Green Field.	30 Nos
9	68.14.5165	Asbestos hand gloves AMC-41, size : 355 mm (14 inch) with superior flannel lining & heat resistance up to 250° C. Shree firepack, Venus or Hindustan composite.	100 Pair
10	68.14.5166	Heavy Duty polyster round sling, 22 mm dia of endless type, capacity 03 Ton, effective length 02 meter. circumfaranace length 04 meter with manufacturers or NABL accredited lab, test certificate, Make Secure Lift, KHR or Green field.	30 Nos

11	68.14.5167	HSS Thread tap set size M-10 x 1.5 mm right hand, as per IS:6175/1992, make Totam, IT or Addision.	20 Sets
12	68.14.5168	Water tank stopper for BEML coaches as per drg no. CRW/SK-613 item no. 1,2,3,4,5 & 6 in assembled condition.	450 Nos
13	68.14.5172	Pneumatic pistol grip impact wrench make CP or IEC or IR Wadco as per annexure attached.	04 Nos
14	68.14.5173	Alluminium Flat head rivet size 5 x 12 mm as per IS : 9089/1999.	260 Kg
15	68.14.5177	Set of ANM Cutting nozzles size-1/16" and 3/64"for nozzle mixing cutter model 102HC ofM/s KOIKF or M/s Ador or M/s ESAB Make (One set consists of 01 No. nozzle of size 1/16"and 01No. nozzle of size 3/64)".	80 Sets
16	68.14.5111	Heavy duty Rigid PVC long bend suitable for 50mm OD Rigid PVC conduit to IS:9537 part"3" with Fire retardent properties (ICF approved) make-Essorke,Indus PNA Indus,Sanco Plastic P.Ltd. precision Plastic,Hirawat Indus,Banco Plastc.	1500 Nos
17	68.14.5135	Screwing DIE,SIZE-1"-2",11TPI,H.S.S.Rockwell Hardness HRC-58-62 SUITABLE for Inderpower eLECTRIC PIPE THREADING mACHINE-140 A.(One set consisting of =04 Nos).	15 Sets

Annexure of tender No.68.14.5154 due on 11.03.2014.

Sr.No.	Part No.	Description	Qty
01	JE070103	Dust Cover	14 Nos
02	JE180109	Insulator tube round	120Nos
03	JE180518	N.O. Moving contact holder	30 Nos
04	JM011880	Brake spring small	22 Nos
05	JM011879	Brake spring big	22 Nos

Annexure of tender No.68.14.5155 due on 11.03.2014

Annexure-A. Requirement of Lux Meter with following features and specifications :

- 3½Digit hand held battery operated.
- Range-2000 to 50000 Lux and above.
- High accuracy in measuring.
- LCD display provides low power consumption.
- Compact, light –weight and excellent operation.

- LCD display can clearly read out even of high ambient light.
Specification:-
 - Display :13 mm (0.5)"LCD.
 - Ranges :0-50,000 Lux, 3 Ranges
 - Operating Temperature : 0 to 50° C.(32 to 122 F).
 - Operating Humidity :Less than 80% R.H.
 - Power supply :DC 9V.Battery.006P. MN 1604(PP3)or equivalent.
 - Power consumption :Approx. DC 2 Ma.
 - Weight : 160g.(0.36LB)with batteries.7
 - Accessories: Required Instruction manual, Test certificate and guarantee card etc. Make- Lutron / Extech.

Annexure of 68.14.5172 due on 11.03.14 Technical specification :

Pneumatic Pistol grip impact wrench Make : CP or IEC or IR Wadco.

Description	Requirement
Drive out put	3/8"
Free speed	11000 RPM
BPM	1620
Working torque	7-68 Nm
Approx Length	146 mm
Approx weight	1-1.2 kgs.
Required Features of Pneumatic Pistol grip impact wrench.	
1.	Rocking dog clutch in oil bath
2.	Built in power regulator
3.	Ergonomic Handle .
9.	<u>Guarantee:</u> Pneumatic angle grinder size should be guaranteed for one year from the date of receipt of the same. The firm should be OEM or its authorization certificate should be enclosed along with supply.

Dy.CMM/CRWS/BPL

ID : dycmmpps@gmail.com