

6849449 dt 18/10/2013

728 (7)  
185

Technical specs for 4 Ports Wireless ADSL CPE ( item d)  
Make: Alcatel, Ericsson, ZyXEL, Siemens, Marconi, Motorola, Lucent

S.No.	Specifications
1-	<b>Hardware Specification</b> □ ADSL port: 1 Nos. of RJ 11 Ethernet port: 4 Nos. of RJ 45 Power input (12VDC 1A) Power switch button Reset button ,WPS button for quick and easy wireless security setup should be Eco friendly wireless. Hardware Wireless on/off button to saves energy by eliminating the wasting of electricity. External detachable antenna
2-	<b>ADSL Compliance</b> ITU 992.1 (G.dmt ) ITU 992.3 ADSL2 (G.dmt.bis) ITU 992.5 ADSL2+ Reach-Extended ADSL (RE ADSL) Annex L/M support
3-	<b>WLAN</b> IEEE 802.11n compliance should be backward compatible with 11b/g Frequency Operation:2.4GHz 64 /128 bits WEP data encryption WPA/WPA2 (Wi-Fi Protected Access) Security Support IEEE 802.1x, External Radius server: EAP-MD5, TLS, TTLS, PEAP Wireless Scheduler Wi-Fi Multimedia (WMM) WPS (Wi-Fi Protected Setup)
4-	<b>Router</b> NAT (Maximum 2048 sessions) SIP ALG pass-through NAT port forwarding PPPoE pass through Dynamic DNS IP Alias DHCP Server/Client/Relay RIP I/ RIP II support IGMPv1 and v2 support, UPnP support ,802.1Q/1P
5-	<b>Firewall</b> Robust and proven SPI firewall with DoS attack protection
6-	<b>Security</b> Multiple VPN (IPSec, PPTP) pass through Packet Filtering URL keyword blocking
7-	<b>Management</b> Embedded Web Configuration TR 069 HTTPS support Logs and Statistics SNMP v1 and v2 with MIB II Remote Management Control: Telnet, FTP, Web, SNMP, and DNS CLI command via telnet/console

M.C.R.

Shuman  
वरिष्ठ खंड अभियंता (दू. सं.)  
(अनुरक्षण) पत्रि, मध्य रेल, जबलपुर  
Senior Section Engineer (Tele)  
M) West Central Railway, Jabalpur

सहा. मंडल सिग्नल एवं दूरसंचार इंजीनियर  
पश्चिम मध्य रेल, जबलपुर  
Asstt. Divn. Sig. & Telecom Engineer  
W.C. Rly., Jabalpur

पश्चिम मध्य रेलवे

8-	Physical Specification
	Environmental Specification
	Operating Temperature: 0°C~40°C
	Operating Humidity: 20% to 90% (non-condensing)
	Storage Temperature: -20°C to 60°C
	Storage Humidity: 20 to 90% RH(non-condensing)
9-	Certification
	Safety: CE ( EN60950-1 , IEC 60950-1) / UL / CSA
	EMI: FCC / CE / C-Tick

*Shuman*  
 वरिष्ठ खंड अभियंता (दू. सं.)  
 (अनुरक्षण) पश्चि. मध्य रेल, जबलपुर  
 Senior Section Engineer (Tele)  
 (M) West Central Railway, Jabalpur

*Mh*  
 सहा. मंडल सिग्नल एवं दूरसंचार इंजीनियर  
 पश्चिम मध्य रेल, जबलपुर  
 Asstt. Divn. Sig. & Telecom Engineer  
 W.C.R., Jabalpur