P.O. 90. 13. 5002.1. 41438 dt 19/3/14

Annexure

Set of steel grit and steel shots for Non stock demand no-96161976 dated 8.1.2013

Sr. No	Description	IS Specification	Size as per SAE system	Equivalent size as per IS system	Quantity
1	Steel grit grade G-25		G-25		3.0 MetricTonne
2	Steel shot grade S-330	IS 4606/1983	S-330	SS-850	3.0 MetricTonne
3	Steel shot grade S-390	IS 4606/1983	S-390	SS-1000	3.0 MetricTonne
4	Steel shot grade S-460	IS 4606/1983	S-460	SS-1180	3.0 MetricTonne
				Total quantity	12.00MetricTonne

Chemical composition: (For all grade)

C	0.6 to 1.25
Si	0.2 to 1.10%
Mn	1.25% max.
Sulpher	0.080% max.
Phosphorus	0.08% max.
Density	7.0gm/ml minimum for Steel shots and 7.6gm/ml minimum for steel shots.
Hardness	40-50 HRC (Average) for steel shots and > 60HRC for steel grits

Sieve Analysis:

(i) Steel grit G-25
- 1.180mm- All Pass
- 0.710 mm- 70%
- 0.425 mm- 80%

(ii) Steel shots(S-330)
- 1.400mm - All Pass
- 1.180mm - 05% max.
- 0.850mm - 80% max.
- 0.710mm - 11% max.
- Pan - 04% max.

(iii) Steel shots(S-390)
- 1.700mm - All Pass
- 1.400mm - 05% max.
- 1.00mm - 80% max.
- 0.850mm - 11% max.
- Pan - 04% max.

(iv) Steel shots(S-460)
- 2.000mm - All Pass
- 1.700mm - 05% max.
- 1.180mm - 80% max.
- 1.000mm - 11% max.
- Pan - 04% max.

AWM (R)
CRWS/BBL

Superintending Engineer (P&C)
CRWS/BBSR