



NOTE

- 1, SUITABLE CUTAWAY TO BE DONE AT SITE FOR ITEMS - 2 & 3 TO SUIT THE FRAME.
- 2 REXINE AND FELT SHOULD BE PASTED TO THE SEAT FRAME WITH APPROVED BRAND OF ADHESIVE
- 3 PITCH OF TAPPING SCREW SHOULD NOT BE MORE THAN 150 MM.
- 4 REXINE SHOULD BE STITCHED IN SUCH A MANNER THAT NO FOLDS ARE VISIBLE AT THE CORNERS.
- 5 THREAD SHOULD BE DYED & BONDED AND THE COLOUR OF THREAD SHOULD MATCH
- 6 COMPREG TO BE TREATED AGAINST FUNGI, TURMITE, MARINE BORERS AND OTHER INSECT ACCORDING TO REQUIREMENT OF PRESERVATION TREATMENT TO IS 5539-69 TYPE-IV (COPPER CHROME ARSENIC COMPOSITION)

REF. DRG. DRAWING DRAWN AS PER DETAILS GIVEN BY SSE CARD.

| NO | QTY | DESCRIPTION | MAT & SPEC |
|----------------|-----|-------------|--|
| 1 | 1 | 10 | FELT 3X30X 3000 APP. IS:1719-88 TAB-1 |
| 39 | 39 | 9 | PAN HD SCREW 8X40 I 15:7169-89 |
| 1 | 1 | 8 | PANEL 1820X550X3 RDSO SPEC CK-513 |
| 26 | 26 | 7 | PLAIN WASHER 5-5 IS:737-86 19000 |
| 26 | 26 | 6 | CSK HD RIVET Ø5X16 IS:737-86 19000 |
| 1 | 1 | 5 | REXINE (SIDE) 150X4800X1 RDSO/2008 CG-07 |
| 1 | 1 | 4 | REXINE (TOP) 560X1850X1 ALNAC-03 |
| 1 | 1 | 3 | COMPREG PLYWOOD 1780X490X4 RDSO/SPEC C-9407 TYPE I |
| 1 | 1 | 2 | DT. PB 550X1820X38 RDSO SPEC CK 607 with Amad slip 1 & 2 |
| 1 | 1 | 1 | FRAME CRW/SK 893 |
| NO OFF ITEM NO | | | DESCRIPTION |
| NO | | | MAT & SPEC |

| | | | | | |
|----------|--|----------|----------|----------|---|
| AWM | <p>MIDDLE AND UPPER BERTH COMPLETE FOR ICF/RCF COACHES SCN TYPE</p> <p>SCALE 1:10, 1:1</p> | III | II | I | <p>FOR CWM 24/11/10</p> <p>WEST CENTRAL RAILWAY</p> <p>COACH REHABILITATION WORK SHOP H52 BHOPAL</p> <p>DRG. NO. CRW/SK 894</p> |
| SSE PUR | | PER ASSY | PER ASSY | PER ASSY | |
| SSE CARD | | | | | |
| JE DRG | | | | | |
| DRN | | | | | |