

**Dy. CMM/CRWS/BHOPAL**

No. 68.14-WB-13

Date : 17.07..2014

Tender to be closed on... **25.07.2014..... at 14:30 Hrs .**

Place Of Delivery : Dy. CMM (CRWS) BPL {AT MAIN STORES}

Delivery Terms : 30 Days / Ex stock

**Note : Rates should be quoted in words as well as in figures also.**

Sr	Tender No	Description	
1	68.13.5858	Heat Convector having adjustable temperature control safety thermal cut off 230 V AC, 50 HZ single phase wattage 1330/2000 w motor capacity 21 w with 3 core flexible cable, 15 A, 3 pin moulded plug of KHAITAN or CROMPTON or BAJAJ MAKE.	04 Nos
2	68.14.5524	CREST for Indian Railway drg. NO. CC26145 Alt 'C' and as per RCF specification No-MDTS 036, Test certificate to be provided with the material.	1400 Nos
3	68.14.5532	Set of spares for Jost make platform Truck. One set consisting as per enclosed Annexure. Make- Jost or similar.	01 Set
4	68.14.5529	Spring Guide for L.S. Beam Drg. No.RCF-CC05139 Alt. b.	300 Nos
5	68.14.5487	Set of fitter for automobile vehicle. One set consisting as per enclosed annexure make-Mico/ Elofic/ fleet gaurd.	01 Set
6	68.14.5479	HRC Fuse Off Tag TIA type 16 AMP, ISI marked Make RBCO, Seimens, L & T, GE Power, C & S, KEL polakkad (RDSO/ICF/RCF approved make)	150 Nos
7	68.14.5481	Press Fit Tube Light Holder (T-5 Holder) Sample to be supplied along with offer.	2200 Nos
8	68.14.5528	Set of Steel Number Punch from 0 to 9; size: 10 mm. Make-RABRO, BRADMA or GROZ.	05 Set
9	68.14.5421	Leather Hand Gloves as per CRWS Document No. WI/SAFETY/006, Specification No. 07, valid from 18.12.2012 (Annexure attached). Firm should submit one pair of hand gloves along with their offer.	600 Pairs
10	68.14.5525	Adjustable wrench size 12" long, opening capacity 35mm, Black finish. Make-Taparia or Stanley or Kennedy.	24 Nos
11	68.14.5265	Ball valve size 50 mm IS : 9890 with ISI marked overall length 145 mm Kranti / Marck / Arch make (Test certificate submit at the time of supply)	10 Nos
12	68.14.5537	Lever Assembly (In assembled condition) to drg no. LB 35419	05 Nos

T. No. 68.14.5532

S.No.	Part No.	Description	Qty.
1.	JM011785	Tube brake assembly	06 Nos.
2.	JE42975	Main Shaft	24 Nos.
3.	JE100202	Oil Seal Size 200 X 300 X 50	12 nos.
4.	E00186	Battery Plug Connector	48 Nos.
5.	JM647170	Tie Rod assembly	06 Nos.

Annexure of T. No. 68.14.5487.

Sr.	Part No.	Description	Qty.
01.	9451037404 Mico	Deisel filter primary for swaraj make forklift	40 Nos.
02.	9451037405 Mico	Deisel filter secondary for swaraj make forklift	40 Nos.
03.	LF 160-60	Fleet guard Lub oil filter for TATA 1613	06 Nos
04.	EK 3975 Elofic	Lub oil filter for TATA 709	12 Nos.
05.	EK 3818 Elofic	Oil filter for TATA 1210	04 Nos.
06.	EK 3908 Elofic	Transmission filter for Godrej forklift	24 Nos.

Annexure of Tender No. 68.14.5421

### Specification of Leather Hand Gloves.

Spec. No..07 of document no. WI/Safety /006 (Rec-01)

Bidder must submit remarks of each and every clause failing which offer may be ignored.

1. **Application:-** These leather hand gloves shall be used in the welding and material handling activities.

2. **Description:-**

The length of hand gloves shall not less than 15 inches.

The hand width size shall be 5.5 inches (Min.0and calf width size 7 inches(Min.)

The gloves shall be made of split leather.

The gloves shall be dyed in dark rust / blue / black colour.

The thickness of leather shall be 1.2mm minimum.

The leather hand gloves should be hard wearing and heat resistance cowhide /buffalo hide.

The gloves shall be so flexible that user must not feel stiffness while doing continuous welding.

The gloves shall have thinsulate insulation lining as intermediate and cotton cloth shall be used for

hand inner lining and fire resistance cloth for calf portion lining. KEVLAR threads shall be used for

stitching purposes. It should be 1729.V-6 cord and single thread breaking load shall not be reinforced with a leather strip and stitched with two rows of Kevlar stitched.

3. **Testing Parameters:-**

Double hole stitch tear strength=50 50kg /sq cm minimum(Method of test LC:8 of IS:5914-1970.)

Shrinkage temperature =90°C minimum (Method of test LC:10 of IS:5914-1970).

Fat content of leather=7% to 10%

Chromium content of leather=3%Min.

Ph Value of aqueous extract=not below 3.5(Method of test LC:18 of IS: 582-1970).

Tear resistance :25 Newton.

Contact Heat resistance: 100°C.

**4. Test Certificate:-**

All of the above tests shall be done from the Govt. lab.like CLRI/ Engineering Institutes/ accredited lab of NABL.

All of above test certificates are required to submit along with their offer. failing which offer shall be ignored.

- 5. Sample:-** Bidder must submit one pair of non returnable sample (s) along with their offer. Failing which the offer shall be ignored.

**DyCMM/CRWS/BPL**

E-Mail ID : [dycmmpps@gmail.com](mailto:dycmmpps@gmail.com)