

58411389

10/11/13

(14)
(9)

1. DIGITAL MULTIMETER

Make : Rishabh

Model : Rishmulti 15 S

3 1/2 Digit, 3100 Counts, Auto Power Off (Power Economising Circuit)
Auto / Manual Ranging, Warning for Blown Fuse & Overload Condition,
Automatic Terminal Blocking System, Min / Max Value Storage, Data Hold
Compatible with PC Connection through RS 232 port thru adaptor
Fitted with Infrared transmitter for data storage and PC communication,
Data storing in Online & Offline mode possible through adapter,
Digital cum Analog Bar graph Indication for better sampling rate (20 reading)
Holster of Soft Rubber for shock & drop protection,
Operable with 9 V battery, Life of Battery: Approx 750 Hrs on-DC mode,
Bat low Indication,

Electromagnetic Compatibility (EMC), IP 50 & IP 20 Protections,
Supplied with lead set, user manual, test & Calibration certificate, Rubber
Holster, Carrying belt

AC Voltage: 30 mV - 1000 V,

DC Voltage: 3 V - 1000 V,

AC Current: 300 uA - 10 A, (Max upto 16 A-Fused)

DC Current: 3 mA - 10 A, (Max upto 16 A-Fused)

Resistance: 30 Ohm - 30 MOhm,

Continuity, Diode Check,

Capacitance: 30 nF - 30 uF,

Frequency: 300 Hz - 100 kHz, ✓✓

% age: 2.0 - 98.0,

Temperature: -200 to +850 Deg C (Pt 100/ Pt1000 input)

Basic Accuracy: 0.25 %

One Year Warranty.

All the 'AC' Voltage and current measurements
have to be of TRMS type: *A. 2/215*

वितरण के द्वारा
D.K.M., W.S. Rly., Bhopal

[Signature]
मानियर संवर्धन इंजीनियर
एकित) स्टोर, प.म. रेल ऑफिस
कोड नं. 58416

This specification is having TRMS measurement as default.

[Signature]
26/11/2014