

INTEGRAL COACH FACTORY, CHENNAI-38	ICF/MD/SPEC-119 ISSUE STATUS:01 REV. No.04 Date : 24-07-2003
SPECIFICATION FOR 2 SEATER/ 3 SEATER RECLINING CHAIRS FOR AC CHAIR CAR & II CLASS CHAIR CAR (NON AC)	
AMENDMENT SLIP NO. : 01 DATED.13-09-05	NO .OF PAGES : 1

PAGE CLAUSE EXISTING REVISED

3	2.16.1	Fibreglass woven cloth as per IS:11273-92 having minimum density of 200 gm/Sq.m or alternate fabric made out of flame resistant fibre shall be provided all around PU foam including between upholstery and cushion as a fire prevention measure	Fibre glass woven cloth as per IS:13128-1991 (PART-1) having minimum density of 206.5/Sq.m as per variety No.20 of Tab.1 or alternate fabric made out of flame resistant fibre to be approved by ICF shall be provided all around PU foam including between upholstery, cushion and back rest as a fire prevention measure.
6	7.2	The chair shall be supplied in properly packed condition so as to avoid any damage during transit, handling and storage. If any plastic material is used for packing, the thickness of the packing material shall not be less than 20 microns.	The chair shall be supplied in properly packed condition so as to avoid any damage during transit, handling and storage. Bio-degradable packing material shall be used. If any plastic material is used for packing, the thickness of the packing material shall not be less than 25 microns.

CONTROLLED BY	PREPARED BY	VERIFIED BY	APPROVED BY
<i>Rov</i>	<i>J. Dooling</i>	<i>Suleman</i>	<i>A/</i>
SSE / D / MS	SME / DSD	DY.CME / DESIGN	CDE/MECH