



S.NO.	A	B	C	D	E	F	DIA.	STRAND	ALUMINIUM FERRUL DIA. (E.F.)	S.W.L.	TENSILE STRENGTH DES. OF WIRE
1	500	500	2400	3400	120	120	32 M.M.	6 X 37	65 MM	9 TONN	1770
2	500	500	2400	3400	120	120	30 M.M.	6 X 37	61 MM	8 " "	1770
3	340	340	1620	2300	100	100	24 M.M.	6 X 37	50 MM	5 " "	1770
4	340	340	1620	2300	90	90	20 M.M.	6 X 37	41 MM	3.5 " "	1770
5	340	340	1620	2300	90	90	18 M.M.	6 X 37	38 MM	3 " "	1770
6	340	340	1520	2200	60	60	16 M.M.	6 X 37	34 MM	2 " "	1770
7	340	340	1520	2200	60	60	12 M.M.	6 X 37	25 MM	1 " "	1770
8	340	340	1520	2200	60	60	10 M.M.	6 X 37	21 MM	1 " "	1770
9											
10											

**NOTE:-**  
MATL:- STEEL WIRE GALVANIZED  
B TYPE FIBRE CORE

TYPE OF ENGINE	WDM2	MATL. SPEC. NO.	SEE NOTE 15.1835/76	ALT. AUTH.	DESCRIPTION	DATE
WEIGHT.		TREAT.		(1) J. J. J.	WIRE ROPE SLING FOR GENERAL LIFTING PURPOSE	14/8/76
SCALE.		REF. DRG.	WDM2SK459R.			
DRP. NO.						
CAT. NO.						
WHERE USED FOR LOUVER MOUNT			D. M. E. D.			
GR. NO. WJ/SK-459 R						