

Reg. 58411585

Specifications of 60 V SPD (SPD/60 V)

DT 30/5/14 (for power supply cum data line)

SN	Items	Required Value
1	Nominal voltage	60 V DC
2	Rated voltage (max. continuous operating voltage)	≥ 70 V DC
3	Nominal current	≥ 1 A
4	Lightn. Impulse current (10/350) Per line	≥ 2.5 kA
5	Nominal discharge current (8/20) per line	≥ 10 kA
6	Voltage protection level	≤ 200 V
7	Bandwidth unbalanced	≥ 1 MHz
8	Case capacitance Line/line	≤ 1 nF
9	Line/PG	≤ 1 nF
10	Operating temperature range	-10° C..... $+ 80^{\circ}$ C
11	Mounting on	35 mm DIN-rail
	Device failure indication	Required.

Gen

Asstt

सॉलियर सेक्टर इन्जीनियर
इंजीनियर

- Note -
1. Make of standard International product like - Phoenix, OBO, DEHN, ERICO, Transector, Furze, Emerson etc.
 2. UL certificate (with Link) / KEMA certificate should be submitted of the product alongwith the technical data sheet with the offer

जे. एस. मीणा
J. S. MEENA

उप मुख्य सामग्री प्रबंधक/जी.एण्ड सी.
Dy. Chief Material Officer/G&C
पश्चिम मध्य रेल, जबलपुर
West Central Railway, Jabalpur

7.3
30/10

पश्चिम मध्य रेल