

WCR

5

SPECIFICATION FOR UNGALVANISED WIRE ROPE

INDENT NO. :- 43096078

DATE - 30.09.2014

DESCRIPTION :-

Double legged wire rope sling with ring at top & hook at bottom as per IS: 2762 of 2009

SAFE WORKING LOAD: - 40 Tons at 90° included angle.

CONSTRUCTION: -

6 X 36 Steel core (I.W.R.C.)

WIRE ROPE: -

Factor of safety shall be 6 with 52 mm dia having minimum breaking load of 1705 KN as per IS: 2266/2002 or latest.

LENGTH: -

6 Mts. (Including ring & hook)

RING SIZE: -

Elliptical type with inner area of 550 X 350 mm as per IS: 2760 or latest

HOOK: -

Hook shall be made high tensile alloy steel conforming to IS: 2759 or latest So the weight of hook is reduced.

INSPECTION: -

By RITES at manufacture's site.

TEST CERTIFICATE: -

A test certificate from government approved test house shall be obtained for the wire rope being supplied after testing and shall be submitted along with the dispatched advice.

*The Specification of Requisition
for stores Requisition No 43096078
is found to be correct.*

Slaty
वरिष्ठ अनुभाग अभियंता
वायरोप & सीटी सेक्शन परेल-90128
Senior Section Engineer
W/R & CT Section PAREL-90128

B
वरिष्ठ खण्ड अभियन्ता (ब्रेक डाउन)
Sr. Section Engineer (Break Down)
कोटा जं. (WCR) Kota Jn.