

पश्चिम मध्य रेल  
West Central Railway

उप मुख्य सामग्री प्रबंधक, सडिपुका/भोपाल  
Dy. CMM/CRWS/BHOPAL

सं. 68.15-साप्ताहिक बुलेटिन-17  
No. 68.15-WB-17

दिनांक 04.12.2015  
Date : 04.12.2015

निविदा प्राप्त करने की अंतिम तिथि 15.12.2015.....समय 14.30 बजे  
Tender to be closed on **15.12.2015** at 14:30 Hrs

सुपुर्दगी का स्थान : उप मुख्य सामग्री प्रबंधक, कार्यालय, सडिपुका/भोपाल  
Place of Delivery : Dy. CMM (CRWS) BPL {AT MAIN STORES}

सुपुर्दगी की अवधि : 30 दिन/तैयार सामग्री  
Delivery Terms : 30 Days / Ex stock.

नोट – दर शब्दों एवं अंकों दोनों में देना अनिवार्य है।

Note : Rates should be quoted in words as well as in figures also.

Sr.	T. No.	Description	Qty
1.	68.15.5251	Bulk head fitting with wire mesh cover for protection of glass for ART/RA and medical coaches, Make-Dollar/Luminaires, Cat Ref.DGB 100,Diamension - 195x115x120 MM or similar.	50 Nos.
2.	68.15.5701	Chemical multi -Parameter field water test kit IS 10500:2012 suitable for testing fluoride, chloride, residual Chlorine Total hardness Iron, Nitrate, PH, Turbidity etc in Drinking water. (Each kit having the capacity to test 100 samples for each parameters.	04 Kits.
3.	68.15.5796	Set of Spares for JOST make PLATEFORM TRUCK. One set consisting as per enclosed annexure .make JOST or similar .	01 Set.
4.	68.15.5809	Moulded case circuit breaker (MCCB) Rating -100Amp/Four pole ,reference no. of C&S make -CD 100 SFMU up ,breaking capacity-37 KA of 415 volt, ICU -100% ICS, Double break switching contact design having elect life of 10,000 electrical operation. Dimension of MCCB should not be more than :WxHxD=120x140x86mm.Make -C&S win break 2 series/Schneider NS range (Merlin gerin range france ) / L&T Desine / ABB T Max. Manufacturer has to submit the test certificate fulfilling all the above technical specs at the time of submitting the tender technical Bids.	50 Nos.
5.	68.15.5884	Twisted twin unsheathed flexible PVC Insulated copper to IS : 694-1990 Latest ,Cross section area 0.5 sq.mm (16/0.20mm) make -Anchor, Skytone, Nicco, Universal, Havells, CCI& RPG	5000 Mtrs.
6.	68.15.5886	M.S. Drain Grid Pipe to drg. no. CRW/SK-251	120 Nos.
7.	68.15.5889	Galvanized Equal Elbow size ½+ ,as per IS: 1879/2010,Table -6 type -6 -type A1/45 degree	360 Nos.
8.	68.15.5890	Galvanized Equal Elbow Size 1 ½ (40 mm), as per IS:1879/2010, table-6 type A1/45 degree.	360 Nos.
9.	68.15.5891	Portable heavy duty impact wrench machine as per specification attached Annexure-"A"	02 Nos.
10.	68.15.5893	Set of Led type indicator lamp with adopter plate suitable for 110 volt AC supply in following colours (a) -Red (with 09 Led)-Yellow(with 09 Led), (c) -	25 Sets.

		Blue (With 01 Led ).One set consist of one number of each colour. Make-Altos or similar.	
11.	68.15.5896	Set of following digital panel meters-(a) Digital panel AC Ammeter ,Model-Rish Eine 1 of Rishabh make,Programmable Rish Eine class -I,True RMS Measurement ,single phase network input -5 AAc ,Thru CT (1600/5A),Display -1600A,Size-96x96,Aux supply -AC-80-300 Volt AC ,Make -Rishabh or similer. (b) Digital Panel DC Voltmeter ,model -Rish Eine +of Rishabh make ,4 digit DC voltmeter ,Size-96x96 ,Range -0-24 Volt DC,Aux Supply -80-300 volt AC ,single phase Network ,ACC class -0.5 ,make -Rishabh or similar. One set consist of 2a + b	08 Sets.

Annexure of T. No. 68.15.5796.

Sr. No.	Part No.	Description	Qty.
01.	JE 070308	Top shaft assembly	06 Nos.
02.	JE 180111	Insulating bush square	12 Nos.
03.	JE 190039	MS Supporting Stud	48 Nos.
04.	FW 3168402	Out Put Flange	22 Nos.
05.	JE 180008	Copper lug size 50 sq. mm.	200 Nos.
06.	JE 070108	Bottom shaft assembly	06 Nos.
07.	JE 050101	Brake shaft spring	12 Nos.

Annexure of T. No. 68.15.5891.

Sr. No.	Technical specification	Description
01.	Drive	Square drive ½+
02.	Std. Bolt size	14 MM
03.	Free Speed	6900 RPM
04.	Working Torque	35-542 NM
05.	Maximum Torque	746 NM Reversible
06.	Air inlet NPTF	¼+
07.	Minimum hose size	10 MM
08.	Over all length	180 MM
09.	Net weight	2.5 Kg approx
10.	Make	Chicago Pneumatic / IR Wadco / IEC make.

E. Mail ID : [dycmmpps@gmail.com](mailto:dycmmpps@gmail.com)

Dy. CMM/CRWS/BPL