

पश्चिम मध्य रेल
West Central Railway

उप मुख्य सामग्री प्रबंधक, सडिपुका/भोपाल
Dy. CMM/CRWS/BHOPAL

सं. 68.16-साप्ताहिक बुलेटिन-07
No. 68.16-WB-07

दिनांक 29.06.2016
Date : 29.06.2016

निविदा प्राप्त करने की अंतिम तिथि 05.07.2016.....समय 14.30 बजे
Tender to be closed on **05.07.2016** at 14:30 Hrs

सुपुर्दगी का स्थान : उप मुख्य सामग्री प्रबंधक, कार्यालय, सडिपुका/भोपाल
Place of Delivery : Dy. CMM (CRWS) BPL {AT MAIN STORES}

सुपुर्दगी की अवधि : 30 दिन/तैयार सामग्री
Delivery Terms : 30 Days / Ex stock.

नोट – दर शब्दों एवं अंकों दोनों में देना अनिवार्य है।

Note : Rates should be quoted in words as well as in figures also.

Sr.	T. No.	Description	Qty
1.	68.16.5468	Supply of Solid PVC door (Door frame with shutter) with all necessary accessories and fitting as per enclosed Annexure-I.	19.31 Sq. Mtrs.
2.	68.16.5469	Handle for Wheel for Hand Brake. Specification No. IS: 210, Grade 15, Drawing No. TLR-3-4-002, Alt. 9 Item No. 7.	50 Nos.
3.	68.16.5472	Socket Accessory's Reversible Ratchet Handle ,1/2"squre drive with rubber Handle, length 255 mm, Make-Taparia, Kennedy/ Jhalani / Gedore. . As per length 240mm,NO teeth 72 Make . Tapariya / Kennedy /Jhalani / Gedore.	20 Nos.
4.	68.16.5480	CSK head slotted screw size M 5 x 40 mm. Full thread to IS:1366-2002, property class 4.8 product grade A with 01 nut M 5, 02 punched washer M 5 to IS:2016, 01 spring washer M 5 to IS: 3063 bright zinc plated in assembled condition (01 set = 04 Item 5 Nos)	50000 Sets.

E. Mail ID : dycmmpps@gmail.com

Dy. CMM/CRWS/BPL


68.16.5468


Annexure - I


Supplying the solid panel PVC door (door frame with shutter) with all necessary accessories and fittings in SSE (W) CRWS NSZ depot.

1. PVC door frame of size 50 x 47 mm with wall thickness of 5mm made out of extruded 5 mm rigid PVC foam sheet mitered at corners and joint with 2 Nos. of 150 mm long bracket of 15 x 15 mm MS square tube, the vertical door profiles to be reinforced with 19 x 19 mm MS square tube of 19 gauge EPDM rubber gasket whether seal to be provided throughout the frame the door frame to be fixed to the wall using MS screw of 65/100 mm size complete.
2. PVC door shutter 30 mm thick factory made solid both side pre-laminated PVC panel door shutter consisting of frame made out of MS tube of 19 gauge thickness and size of 19 mm x 19 mm for styles and 15 x 15 mm top and bottom rails. MS frame shall have a coat of steel primer of approved make and manufacture. MS frame covered with 5 mm thick head molded pre-laminated PVC foam sheet "C" channel.

Door size	Numbers	Area (in Sqm)
0.76 x 2.08 mtr.	1	1.5808
0.78 x 2.08 mtr.	1	1.6224
0.76 x 2.11 mtr.	2	3.2072
0.78 x 2.10 mtr.	1	1.6380
0.79 x 2.10 mtr.	1	1.6590
0.80 x 2.00 mtr.	6	9.6000
	Total	19.3074


SSE (W) CRWS NSZ
सडिपुका, भोपाल
(SSE (W) CRWS BPL)


XEN (C-II) BPL
Executive Engineer (C.II.)
CRWS, Bhopal


Dy. CE/CRWS/BPL
उप मुख्य अभियन्ता
सडिपुका, भोपाल