



	x	y
D	0	0
A	63.84	49.89
B	68.83	53.40
C	155	36
D	77.33	121.54

Dimension 'R'
For LH - 25
For RH - 32

- NOTE:
- (1). MACHINED ALL OVER Rz 25
 - (2). ALL DIMENSIONS ARE IN MM.
 - (3). ALL EDGES SHOULD BE CHAMFERED BY 3X45°.
 - (4). ALL FACES SHOULD BE MACHINED.
 - (5). STEP IS NOT PERMITTED AT ANY PLACES.
 - (6). FOR UNSPECIFIED TOLERANCE Ref. IS: 2102 FINE
 - (7). THIS DRG. SUPERSEDES DRG. NO. 1209-01.312-047
 - (8). DRILL HOLE CAN BE DONE DURING FINAL MACHINING TO DRG. NO. 1209-01-112-005.

T211/045		REF. NO.	PART DRG. NO.	DESCRIPTION	NO/ LOCC	MATL.	SPECN.	Weight EACH IN KG.
C & D Nos.				MOTOR SUPPORT RH & LH MODIFIED	4+4	63 THK STEEL PLT.	IS 2062:2011 G. E410 Dty 'C'	12
DIMENSION 116 DELETED. NOTE B AND WEIGHT (2 KG. ADDED) DESCRIPTION		DRAWN	[Signature]	ASSLY DRG. REF. 1209-01.012-011 Ref. 20 MOTOR SUPPORT RH & LH (MODIFIED)	CHATTARANJAN LOCOMOTIVE WORKS			
		CHECKED	[Signature]		ELDO(M)			
		SSE	[Signature]		USED FOR LOCCS WAP-7 & WAG-9			
		AME/D	[Signature]		DRAWING NO.			
DY.CEE/ D-II DATE: 29.5.11 N.T.S. RDSO L. NO. EL/31.35/2 Dtd. 29/05/2014				MOTOR SUPPORT RH & LH (MODIFIED)	1209-01.412-186			
① ALT. NO.					ALT.			