



NOTE:  
 (1) MACHINED ALL OVER RZ 25.  
 (2) ALL DIMENSIONS ARE IN MM.  
 (3) ALL EDGES SHOULD BE CHAMFERED BY 3X45°.  
 (4) ALL FACES SHOULD BE MACHINED MIN CMC.  
 (5) STEP IS NOT PERMITTED AT ANY PLACES.  
 (6) FOR UNSPECIFIED TOLERANCE REF. IS R102 FINE.  
 (7) THIS DRG SUPERSEDES DRG. NO 1209-01.412-122.  
 (8) ALL EDGES SHOULD BE SMOOTHENED BY USING GRINDING WHEEL.  
 (9) FINAL PROFILE & DRILL HOLE 26 CAN BE MADE DURING MACHINING TO DRG. NO. 1209-01.112-039.

C & D Nos.	REF. NO.	PART DRG. NO.	DESCRIPTION	NO/ LOCS	MATL.	SPECN.	Weight EACH IN KG.
			SUPPORT	4	63 THK STEEL PLT.	IS 2068:2011 Gr. E410 QUALITY 9.8	13.25
			DESCRIPTION				
			ASSLY. DRG. REF. 1209-01.112-121 REF 1				
			CHITTARANJAN LOCOMOTIVE WORKS				
			ELDD(M)				
			SUPPORT (NEW)				
			USED FOR LOCUS WAP-7 & WAG-9				
			DRAWING NO. 1209-01.412-187				
			ALT.				
			DRAWN: ANGAD				
			CHECKED: [Signature]				
			SSE: [Signature]				
			APR/D: [Signature]				
			DY.CEE/D-II: [Signature]				
			DATED: 21/10/2014				
			N.T.S.				
			DESIGN L. NO. EL/1135/2(BRAKE LEVER) DL 200814				