

Revised Specification of Forklift

S.No.	Parameter	Description
1.	Rated Capacity	3000KG at 500 mm load centre
2.	Capacity	3000KG at 500 mm load centre at ground level and upto 3300mm lift height without attachments.
3.	Mast	Type of mast 3 Stage Overall Mast Height 2400 mm Maximum Fork Height 5350 mm Free Fork Height 1765 mm Overall Extended mast Height with LBR 6570mm Tilt Angle degree (Forward/Backward) 6/6
4.	Major Dimensions	Length to face of forks 2730mm Overall width 1230mm Turning Radius 2475mm Canopy Height 2150mm
5.	Forks	Length x Width x Thickness mm 45x125x1070 Fork Spread 240-965
6.	Performance	Travelling Speed Km/h 17/18 Hoisting Speed mm/sec 500/550 Lowering Speed mm/sec 450/400 Gradability % 20/20
7.	Engine	Indegencous, four cylinder, 4 stroke, 3300cc, BS-IV Industrial diesel engine with 12V electrical system.
8.	Transmission	Automatic
9.	Steering	Hydrostatic Power
10.	Tyre	Solid, Front 2nos /rear 02 nos
11.	Standard Accessories	1. Set of lights (02 front/ 02 rear) 2. Signal Lights(02 front/ 02 rear) 3. Load back rest 4. Reverse Alarm 5. Seat Belt 6. Tool Kit 7. Overhead Guard
12	AMC/Warranty	<u>AMC will not be in scope and Warranty required for one year.</u>