



NOTE:-

1. KEPT BLANK.
2. METAL BONDED RUBBER PAD SHALL BE MANUFACTURED AS PER STR NO. 20 MISC.-95 REV. 3.
3. ALL 2mm RADII HAVE BEEN PROVIDED SO AS TO REMOVE BURRS & SHARP EDGES.
4. DIMENSIONS MARKED THUS \* TO BE GAUGED DURING INSPECTION.
5. PUNCH, NAME OF THE MANUFACTURER, MONTH & YEAR, L-30 (FOR LIFE OF PADS IN MONTHS) AT MARKED LOCATIONS IN 6mm TYPE.
6. STEEL PLATES TO BE PAINTED WITH "SIGNAL RED" (AS PER IS:5-1994, No.537)

ITEM-3

4	TOP PLATE.	4	-	1S: 2062 Fe 410 WA	
3	STIFFENING PLATE.	4	-	1S: 2062 WA Fe 410 WA	SEE NOTE
2	RUBBER PAD.	4	-		ND-2
1	BOTTOM PLATE.	4	-	1S: 2062 WA Fe 410 WA	

SUPERSEDED BY		DATE	
CASNUB 22W (WITH MODIFIED ADAPTER), 22W(M), 22NL, 22NLB, 22HS & LCCF 20(C) BOGIE		22NL, 22NLB, 22HS & LCCF 20(C) BOGIE	

MODIFIED ELASTOMERIC PAD

⑦	-	CONTR-06035	LCCF 20(C) BOGIE ADDED IN BLOCK & DRG. REVISED.	5/06
ALT. ITEM	AUTHY.	DESCRIPTION	DATE	ASSEMBLY DRAWING

B.G.	R.D.S.O.	GROUP	WD-95005/S-1
[w]			

CHECKED	DRAWN	V.S.jindl	1.95
TRACED	J.SHEET		